## ADAIR COUNTY COMMISSION MINUTES TUESDAY, JULY 1, 2014

Continued from page 385

IN REF. ORDER NO 6 Missouri Highways and Transportation Commission permit to Work on Right of Way (Non-Local Government Projects)

	60 (Nov.03-11) RFC	FIVED
	MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION	
	PERMIT TO WORK ON RIGHT OF WAY	1 2014
	NON-LOCAL GOVERNMENT PROJECTS ADAID OF	
	ADAIR CO	UNTY CLERI
	NE District Permit No	
	1711 Highway 61 South 02- Driveway II-Street Route 63 County	Adair
	Hannibal, MO 63401 (Type of Work) City Kirksville	
	Inspector TAROD Murk Issued Log Points	
	Phone 6i0-355-8268 Expires GPS Begins N V	v _
	RMS Scatt Thomp2011 Released: GPS Ends N	w
	Speed Limit mph	1
	Intersection/Stopping Sight Distance	
	Northbound/Eastbound Live Let Liberti	
		Feet
	North from Dogwood Lane & Rte. 63 Intersection.  (State highway, County road, City street or County Line)	
	Description of work:  Applicant is allowed to re-construct a portion of Laurel Lane to Rite 63 during the bridge replacement	on
	Applicant is allowed to re-construct a portion of Laurel Lane to Rise. Bit during the brings representation Laurel Lane. This will be a temporary approach to Rise. 63 and must be removed when the bridge pro-	niect is
	completed. The Adair County Commission is responsible for the construction, removal and cost of the	e
	annosch	
	a religional to cognized to install 40.50 feet of 15 inch cognizated metal or double walled plastic pipe.	nadway
	Applicant is required to install 49-50 feet of 15 inch corrugated metal or double walled plastic pipe.  (3):1 slopes to be maintained on histope of centrance. Entrance to be graded so drainage goes into notice and design property. Right of way to be left in uniform condition. All greas that are disturbed sha	ll be
	Applicant is required to install 46-90 feet of 15 inch corrupated metal or double walled plastic pipe.  (3): a lones to be maintained on inslope of entrance. Fortance to be graded so drainage possiblo or duck and drains properly. Eight of way to be left in uniform condition. All areas that are disjurced shall be uniform to the condition of the property of the condition of the c	or
	Applicant is required to install 40.60 feet of 15 inch corrupated metal or double walled plastic pipe.  (3) I slopes to be maintained on inslope of entrance. Entrance to the grade so detained, poss into a dich and drains properly. Right of way to be left in uniform condition. All areas that are disturbed sha seeded and mulched. Applicant is responsible for maintaining proper Traffic Control when personned requirement are on the roadywar. Anological is responsible for conditioning all tilly companies before we.	or
	Applicant is required to install 40-50 feet of 1.5 inch corrupted metal or double walled plastic pipe. Oil 3 slopes to be maintained on Instalpon of entrance. Fatzona to las grades in artialange post and table and drains grocerly. Right of way to be left in uniform condition. All areas that are disturbed senered and multiple Applicant is responsible for maintaining pumper. Traffic Control whom personnal equipment are on the roadway. Applicant is responsible for contacting all utility companies. before we in MoDIT right or drawy. All work to meat the approval of MoDIT.	or
	Applicant is required to install 40-50 feet of 15 inch corrupted metal or double walled plastic piece.  (2) 1 slopes, to be maintained not instalpos of entrance. Extraorac to be graded as natialage pace in ordinare. Extraorac to be graded as natialage pace plant of the hard drains property. (Sight of way to be left in uniform condition. All areas that are disturbed senered and multiple Applicant is responsible for maintaining purper. Inffice. Control when personnel equirement are on the roadway. Applicant is responsible for contacting all utility companies before we not MoDOT right orway. All works to meet the approval of MoDOT.  Emsion control is the responsibility of the applicant.	or
	Applicant is required to install 40-50 feet of 1.5 inch corrupted metal or double walled plastic pipe. Oil 3 slopes to be maintained on Instalpon of entrance. Fatzona to las grades in artialange post and table and drains grocerly. Right of way to be left in uniform condition. All areas that are disturbed senered and multiple Applicant is responsible for maintaining pumper. Traffic Control whom personnal equipment are on the roadway. Applicant is responsible for contacting all utility companies. before we in MoDIT right or drawy. All work to meat the approval of MoDIT.	or
	Applicant is required to install 46-80 feet of 1.5 inch corrupted metal or double welled plastic pipe.  17.1 slopes to be maintained on instalpon of entrance. Fattornan to be graded as notalined passes that or dick and drains promoting the pipe of the way to be left the uniform monition. All areas that contributed and sended and mixed as monety. Fight of way to be left the uniform monition. All areas that contributed as medical and mixed the promoting of the pipe of the promoting and utility companies before we on MoDOT right of way. All work to meet the approval of MoDOT.  "Applicant also agrees to the attached document provided by Arry Crawford."	or
	Applicant is required to install 40-50 feet of 15 inch corrupted metal or double walled plastic piece.  (2) 1 slopes, to be maintained not instalpos of entrance. Extraorac to be graded as natialage pace in ordinare. Extraorac to be graded as natialage pace plant of the hard drains property. (Sight of way to be left in uniform condition. All areas that are disturbed senered and multiple Applicant is responsible for maintaining purper. Inffice. Control when personnel equirement are on the roadway. Applicant is responsible for contacting all utility companies before we not MoDOT right orway. All works to meet the approval of MoDOT.  Emsion control is the responsibility of the applicant.	or
	Applicant its required to install 46-Bit Cent of 1.5 inch corrupated metal or double walled plastic pipe.  (3) 1 slopes, to be maintained on instance, or extraor, or large region or distance of the property	or
•	Applicant is required to install 46-BO feet of 1.5 linch corrupted motal or doubles welled plastic pile.  10.1 slopes to be mischand on installance a carrier or the control of the grade as declarance pages. Into a click and dealers ground, properly on the control of the properly of the control of the cont	or
•	Applicant his required to install 46-Bit Cent of 1.5 inch corrupated metals or double walled plastic pipe.  (3) 1 slopes to his maintained on instance, or attender to the control of the	or
e1	Applicant is required to install 46-80 feet of 1.5 inch corrupted motal or double welled plantic pipe.  1/1 slopes to how ministand on installance of extraors or the granded an draining appear in the hot of string smoothy. Begin of way to be left in uniform continue. As areas that are distanced and sanded and ministanced areas that are supported for the property of the property o	or
	Applicant is required to install 46-Bit Cent of 1.5 inch corrupted motals or double walled plastic pipe.  (1) 1 slopes to be maintained on instalpon of entrince. Extrance to be graded as relating appeals into a click and drains properly appeals from a click and drains properly appeals from a click and drains properly appeals from a click and drains properly appeals for a click and drains properly appeals from the click and t	or
e1	Applicant is required to install 46-Bit Cent of 1.5 inch corrupted motal or doubles welled plastic piles.  (1)*: slopes to be mischisoland on instalepool extension. Extension to be granted as challenge possibility and characteristic properties of the properties of	or
	Applicant is required to install 46-Bit Cent of 1.5 inch corrupted motals or double walled plastic pipe.  (1) 1 slopes to be maintained on instance, or extreme the region of the control of the property of the control of the con	or
•	Applicant is required to install 46-Bit Cent of 1.5 inch corrupted metal or doubles welled plastic pile.  (1) 1: slopes to be mischisated on install one of extreme to the greatest as relatingue pass since and characteristic productions of the contraction of th	or
	Applicant is required to install 46-Bit Cent of 1.5 inch corrupted metal or doubles welled plastic pile.  (1) 1: slopes to be mischisated on install one of extreme to the greatest as relatingue pass since and characteristic productions of the contraction of th	ineral  / Y  (Date)
	Applicant is required to install 46-Bit Cent of 1.5 inch corrupted metal or doubles welled plastic pile.  (1) 1: slopes to be mischished not instale, not extract to the grades as nationage pass short acts and drains around. Politic divay to be left in uniform. The property of the prope	ineral  / Y  (Date)
	Applicant is required to install 46-80 feet of 1.5 inch corrupted motal or double welled plastic pipe.  1/2 slopes to be maintained on instance, or extraor or the grade an draining appeals into a rich and drains around; possible of way to be left in uniform monition. All around his model and draining around a proper or the property of the property	in the off crising in the critical in
#0	Applicant is required to install 46-Bit Cent of 1.5 inch corrupted metal or doubles welled plastic pile.  (I) 1: slopes to be michicaled on instalpon of earthrone. Extraorac to be graded as incharging peak into a city of the property of t	in the off crising in the critical in
	Applicant is required to install 46-Bit Cent of 1.5 inch corrupted motal or doubles welled plastic pipe.  1/2 1 slopes to his maintained on instalpon of entrance. Extraora to its agrades a notalizage pages into a click and drains promoting the pipe of the way to be left the uniform produce. All areas in that can distalpone and another produced the produced of the pipe of the	in the off crising in the critical in
	Applicant is required to install 46-Bit Cent of 1.5 inch corrupted metal or doubles welled plastic pile.  (I) 1: slopes to be michicaled on instalpon of earthrone. Extraorac to be graded as incharging peak into a city of the property of t	in the off crising in the critical in
\$ .	Applicant is required to install 46-Bit Cent of 1.5 inch corrupted motal or doubles welled plastic pipe.  1/2 1 slopes to his maintained on instalpon of entrance. Extraora to its agrades a notalizage pages into a click and drains promoting the pipe of the way to be left the uniform produce. All areas in that can distalpone and another produced the produced of the pipe of the	in the off crising in the critical in
e e	Applicant is required to install 46-Bit Cent of 1.5 inch corrupted motal or doubles welled plastic pipe.  1/2 1 slopes to his maintained on instalpon of entrance. Extraora to its agrades a notalizage pages into a click and drains promoting the pipe of the way to be left the uniform produce. All areas in that can distalpone and another produced the produced of the pipe of the	in the off crising in the critical in

## SSRN BACKER DI.   TARKE LESS'F IR.   GP FIGHAL   ## SSRN BACKER DI.   TARKE LESS'F IR.   GP FIGHAL   ## SSRN BACKER DI.   TARKE LESS'F IR.   GP FIGHAL   ## SSRN BACKER DI.   TARKE LESS'F IR.   ## SSRN BA	616.8.	.1 (TA-1) W	ork Beyon	d the Sho	ulder on	Divided and	d Undivide	d Highways
### SPESS OF THE PROPERTY OF T						OPTIONAL		ER SPACING (ft.)
Solid   Tool	SPESD				(T2)	LENGTH (ft.)	Tapers	Work Areas
See a	0-35	200	200					1050
So S	40-45	350	500					
The contract weight based in 18 is, become to exceed weight place.  ROAGNAY TYPE  BIGHT  WORK 2016  LEROHT  FORTING  FOR	50-55							
ROGAGNATYPE  ROGAT  WORK ZONE  WORK ZONE  LARCHTILS  FESTAL  F								
HEGHT LUNCHUM.  FORTIAL COVIDED Protest  SM.  FORTIAL COVIDED COVIDED PROTEST  FORTIAL COVIDED PROTEST  On multi-lunc, divided highways, signs advising of shoulder work or the condition of the shoulder should be  condition of the shoulder should be  condition of the shoulder should be  fortial covider should	f Shoulder	tager length based o	on 10 ft. (scandard si	ocuster wisten) of	set 2 Larme to	oer length based on 1	2 ft. (standard tens	e width) offset
PRODUCTION OF THE PROPRIES AND THE PROPR	ROA	<b>GWAY TYPE</b>	SIGN HEIGHT	WOR	KZONE			records.
RUINAL INVOIDED Properties  RUINAL INVOIDED Propert  RUINAL INVOIDED Propert  Propert  S but  The work variables or exporperature suboulder work bytes adjustment and recently  Communication of the suboulder suboulder suboulder suboulder work bytes adjustment  On mutal-inate, divided highways, signs advising of thouselves work on the condition of the suboulder subo	URBAN		1' Portable			NORTH NAME	, .	Work Spa
REGIOLAL DIVIDUAL  Prignt 4 3 M.  If such visibiles or equipment are located on the chief, and the price of price of the chief, and the chief of the chief			1' Portable	-	10	<b>建</b>	(2),647	1
The Work valicities or supportant are located on the chooled, refer to appropriate and subsolute work years appropriate a subsolute work years appropriate absoluted work years approximate, and a subsolute work years approximate, and a subsolute work years approximate and a subsolute work years approximate and a subsolute work years and a subsolute work years and a subsolute work years and a subsolute work on the potential subsolute. If work is being preference in the medical subsolute. If work is being preference in the medical subsolute. If work is being preference in the medical subsolute. If work is being preference in the medical subsolute. If work is being preference in the medical subsolute. If work is being preference in the medical subsolute. It would be subsolute for being the subsolute where the work space is absolute. Beyond the distal lines, or behind the cuts. Should the morbal years have a shoulder, then 13 ft. or more though yor in have a shoulder, then 13 ft. or more though yor in have a shoulder, then 13 ft. or more though yor in have a shoulder, then 13 ft. or more though you have a shoulder, then 13 ft. or more though you have a shoulder, then 13 ft. or more though you have a shoulder, then 13 ft. or more though you have a shoulder, then 13 ft. or more though you have a shoulder, then 13 ft. or more though you have a shoulder, then 13 ft. or more though you have a shoulder, then 13 ft. or more though you have a shoulder, then 13 ft. or more though you have a shoulder, then 13 ft. or more though you have a shoulder than 13 ft. or more though you have a shoulder than 14 ft. or more			7 Post		-			8
Mender withchites or equipment are incented on the shoulder, story on perspectate shoulder work typical applications.  On multi-lame, divide highways, signs ordinated of shoulder work or he is expected only in the story of the because of the story of t	RURAL I	UNDIVIDED	5' Post	3	м.			
Detours.	If work is signs and of travel paragraps.  The SHG may be 15 ft. or shoulder the curb shoulder clips of 15 ft. or shoulder clips of 15 ft. or shoulder clips of 15 ft. or shoulder clips to 15 ft. or shoulder clips to 15 ft. or shoulder clips to 15 ft. or stobe used lights or 0 ft. or sign.  Other a lice of t sign.	is being perform ay be required fel based on the for ho, ho.  OULDER WOR ominded where it was a month of the form of the fel based on the form of the fel based on the fel based	or both direction illowings  K AHEAD siggs he work space is degle of any chile, or both line, or bot	is said and a said this said the said this said the said this said the said this said the said the said this said the said the said this said the s	1 00 00 00 00 00 00 00 00 00 00 00 00 00	0 F 0 1 1 1 1 1 1	5	FOLIDA

320.00	210.00	100-1	Bek. C		100-177 03
7) NEWCOMER & A.M. NEWCOMER	FEW. EASW.T.  PERMINING IT.  PERMINING IT.  PERMINING IT.  PERMINING IT.  NEW R/W.T.	All A COL	NEW RAW	TGZN. R15	
RANDY E NEW	\$255 \$255 \$455	OCT.	60 00 + 89 00 - 00 + 89		03+
NE# 27	00.005 00.005		+	County 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
LAUGEL LANE SW # 20-77EE   DRIVERA TEZN 10-007 GAREE LANDUT 11-007	230.00-1917 00-00	CONTINUE OF THE ACT	765-00-06-185-00-06-06-06-06-06-06-06-06-06-06-06-06-	20 TIPE I DRIVERAY 20 TIPE I DRIVERAY 20 TIPE I DRIVERAY 30 TIPE I DRI	OU CHOCKION
74.50.30 74.		27:152 27:151 2:41:52 3:41:52 3:41:52	00.00+5251 00.00+5251	3500 Dis	2418 - 2400 0402 - 2418 - 240
26,02+ r	91		Section of the sectio	M. ESM.T. 1 N. 195 LT. 1 N. 195 LT. 1 N. 195 LT. 1 N. 195 LT. 1 L. 5 HS.3. 1 N. 195 LT. 1 N.	CLASS A ENCANTION CLASS A ENCANTION CLASS BANKERI CLASS BA
1,44	0+19 4051 1604 165-19 1604 1604 1604 1604 1604 1604 1604 1604	150.00	COPE LINE	15.91 6. KER REW. 1. 20.56 AC. REWAINING RT. 20.56 AC. REWAINING RT. ARTER CORNER COMMON TO SE SERVEY PART RT. 15.153.54 5.399.57 RCOROLO IN SERVEY.	300
A See See See See See See See See See Se	e he	& FROUTE 63	\$ \$000 m	8 8 8 1 00 1 00 1 1 00 1 00 1 00 1 00 1	N 1 N 1 N 1 N 1 N 1 N 1 N 1 N 1 N 1 N 1
(a)	827	1 1810	200.00 SEE	2 FOR ENTRANCE®  6.4. FOUND   22 4.27	

ATTEST:

County Clerk

Presiding Commissioner

Page 386